



Decorative protection for porous and textured concrete



TECHNICAL DATA BULLETIN

OKON PAINTBOOSTER™ WATER REPELLENT ADDITIVE FOR LATEX PAINT OR STAIN

PRODUCT DESCRIPTION

PAINTBOOSTER adds long-term water repellency to latex paint or stain. Water beads-up on a painted surface containing PAINTBOOSTER like water beads up on a newly waxed car. As it repels water, PAINTBOOSTER reduces premature paint failure, wood rot and mold growth. And PAINTBOOSTER does not affect the color, reduce the coverage or increase the cost of paint or stain because it makes paint go further.

In addition, PAINTBOOSTER:

- Reduces brush and roller marks by improving flow and leveling
- Reduces lap marks, especially when painting in direct sunlight
- Reduces dirt-pickup and staining and makes the surface easier to clean

Coatings enhanced with PAINTBOOSTER are ideal for areas subject to moisture condensation:

- window sills, garage doors, fences and gates, siding, outdoor furniture
- porous materials like stucco, concrete blocks, cement, wood, plaster and adobe.

FEATURES

- Combines proprietary water-repellent with 100% acrylic resin to enhance the performance of any exterior latex or stain.
- Repels water by reducing the surface tension of the dried coating.
- Can be added to interior latex paints to resist water spotting and improve washability.
- Maybe recoated and touched-up
- Very low odor, low VOC and cleans up with soap and water.
- Can be added to water based paints and solid or semi-transparent stains
- Long lasting water repellency - 3-5 years depending on quality of coating and exposure conditions

TECHNICAL DATA

- Chemistry Acrylic micro-emulsion
- Weight Solids 33%
- Product type Water-base
- VOC <50 g/L
- Specific gravity 1.02
- Breathable YES - ASTM 1653
- Flash point N/A
- Viscosity <500 - 700 cps

USE INSTRUCTIONS:

PAINTBOOSTER is a water repellent additive used in the finish coat of latex paint or stain. Select the proper coating (paint or stain) for the job and follow recommended surface preparation. If painting, prime previously unpainted surfaces with a proper primer. After stirring the paint or stain thoroughly, combine PAINTBOOSTER and the paint/stain in a container large enough to hold the combined volume of four-parts coating and one-part PAINTBOOSTER (example 5 quarts total : 1 gal. Paint + 1 qt. PAINTBOOSTER). Mix thoroughly and apply according to coating manufacturer's application instructions. If spraying, protect adjacent areas from overspray. Follow coating manufacturer's clean up instructions.

PACKAGING CODES

Product No.	Package	Wtg. (Lbs.)	UPC
OK-814	Quart	2.5	7 49505 81004 1
OK-811	Gallon	9.0	7 49505 81001 0

LIMITATIONS

- Do not mix with oil-base paints or stains.
- In two coat applications over previously painted or non-porous surfaces.
- PAINTBOOSTER is not recommended for areas subject to foot or vehicular traffic, subject to immersion or for use in clear varnishes, primers or two-component paints.
- PAINTBOOSTER may slightly increase the sheen/gloss of the coating because of its high acrylic content. .
- Touch-up must be performed using the product mixed with the same ratio of PAINTBOOSTER.
- On non-porous or extremely smooth surfaces- metal, glazed tile, glass, - PAINTBOOSTER water repellency may cause touch-up paint to crawl or resist leveling. If crawling occurs, wipe the area with cleaner or lightly scuff sand to temporarily reduce the surface tension before applying the touch-up paint.

THE PERFORMANCE OF OKON PAINTBOOSTER IS DEPENDENT UPON STRICT COMPLIANCE WITH MIXING INSTRUCTIONS AND APPLICATION RATES REQUIRED BY THE COATING.

PRECAUTIONS

PERSONAL PROTECTION – Chemical resistant plastic or rubber gloves and safety glasses or chemical goggles should be worn when spraying. Wear a NIOSH-approved respirator if mists are present.

FIRST AID

EYES - Rinse thoroughly for 15 minutes. Get immediate medical attention.

INGESTION – Call a physician immediately. Only induce vomiting at the instruction of a physician.

INHALATION – If experiencing difficulty breathing remove the individual to fresh air. If symptoms persist seek immediate medical attention.

SKIN CONTACT – Flush with water for at least 15 minutes. Launder clothing before reuse. If skin irritation persists seek medical attention.

WARNING!

KEEP OUT OF REACH OF CHILDREN

STORAGE - Keep from freezing



Manufactured and distributed by:

Rust-Oleum Corporation

11 E. Hawthorn Pkwy.

Vernon Hills, IL 60061

(847) 367-7700

www.okoninc.com www.rustoleum.com

The information contained in this bulletin was the best available at time of publication but may be superseded by revisions. Contact Rust-Oleum to determine if updates are available.